



CLCR30

CONTINUOUS RIM

TILE - HARD DENSE MATERIALS

Classic

Cat® Classic super hot press continuous rim blades are a precise cutting diamond blade designed for hard materials and tiles. Good quality diamond grit and high diamond concentration ensures good blade life whilst offering a fast, smooth, chip free cut on the correct applications. The finish of cut and blade life increases with water as a coolant whilst cutting harder materials. The CLCR30 is the ideal choice for contractors wanting a high quality, fast, long life blade.

ATTRIBUTES

- 1.5X LIFE - 1.5X SPEED
- HIGH QUALITY FINE DIAMOND GRIT
- ENHANCED PERFORMANCE & LIFE
- SUPER HOT PRESS TECHNOLOGY
- FULLY HARDENED & HEAT TREATED STEEL CORE
- FAST, PRECISE & CHIP FREE FINISH
- CONTINUOUS RIM DESIGN.

APPLICATION

★★★★	PORCELAIN, CERAMIC TILES, TERRACOTTA, HARD SLATE, MARBLE.
★★★	ENGINEERED ARTIFICIAL STONE, GRANITE, QUARTZITE, CLAY ROOF TILES, QUARRY TILES, TRAVERTINE.
★★	PORCELAIN GRADE 5, VITRIFIED CLAY PIPES, PORPHYRY, BASALT, SOFT SLATE, LAVA ROCK, PUMICE.
★	DENSE CLAY PIPE, CLAY PAVERS, VITRIFIED CLAY PIPES.



DRY CUTTING



WET CUTTING



PRODUCT		DIAMETER		SEGMENT HEIGHT		SEGMENT WIDTH		MAIN ARBOR - BORE		REDUCING RINGS INCLUDED		MACHINES USED
PART NO	CODE NO	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	
DA11024	CLCR30105	105	4	7	0.276	1.6	0.063	20	20mm	20 - 15.88	20mm - 5/8	
DA11025	CLCR30110	110	4 1/3	8	0.315	1.6	0.063	20	20mm	20 - 15.88	20mm - 5/8	
DA11026	CLCR30115	115	4 1/2	7	0.276	1.6	0.063	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20mm, 7/8 - 5/8	
DA11027	CLCR30125	125	5	7	0.276	1.8	0.071	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20mm, 7/8 - 5/8	
DA11028	CLCR30150	150	6	7	0.276	1.8	0.071	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20mm, 7/8 - 5/8	
DA11029	CLCR30180	180	7	7	0.276	1.8	0.071	25.4	1	25.4 - 22.23, 25.4-20, 25.4 - 15.88	1 - 7/8, 1 - 20mm, 1 - 5/8	
DA11030	CLCR30200	200	8	7	0.276	2.0	0.079	25.4	1	25.4 - 22.23, 25.4-20, 25.4 - 15.88	1 - 7/8, 1 - 20mm, 1 - 5/8	
DA11031	CLCR30230	230	9	8	0.315	2.0	0.079	25.4	1	25.4 - 22.23, 25.4-20, 25.4 - 15.88	1 - 7/8, 1 - 20mm, 1 - 5/8	
DA11032	CLCR30250	250	10	8	0.315	2.0	0.079	25.4	1	25.4 - 22.23, 25.4-20, 25.4 - 15.88	1 - 7/8, 1 - 20mm, 1 - 5/8	
DA11033	CLCR30300	300	12	10	0.394	2.2	0.087	25.4	1	25.4 - 22.23, 25.4-20, 25.4 - 15.88	1 - 7/8, 1 - 20mm, 1 - 5/8	
DA11034	CLCR30350	350	14	10	0.394	2.4	0.094	25.4	1	25.4 - 22.23, 25.4-20, 25.4 - 15.88	1 - 7/8, 1 - 20mm, 1 - 5/8	



WARNING: This product can expose you to "Nickel" which is known to the State of California to cause cancer and birth defects.
ADVERTENCIA: Este producto puede exponerlo a un "Níquel" que el Estado de California sabe que causa cáncer y defectos de nacimiento.
AVERTISSEMENT: ce produit peut vous exposer à un "Nickel" connu de l'État de Californie pour provoquer le cancer et des malformations congénitales. www.P65Warnings.ca.gov



©2023 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. C6 DIAMOND LLC, a licensee of Caterpillar Inc.

SILICA DUST: Workers who are exposed to respirable crystalline silica dust are at increased risk of developing serious silica-related diseases. It is necessary to use saws and other machinery that is equipped with an integrated water delivery system that continuously feeds water to the blade. Operate and maintain all tools in accordance with manufacturer's instructions to minimize dust emissions and always wear the correct ventilator. For more info visit: www.osha.gov/sites/default/files/publications/OSHA3681.pdf