



# MXT30

## **TURBO CONTINUOUS RIM**

## HARD MATERIALS

**200** Trade





**DRY CUTTING** 



**WET CUTTING** 











Cat® 200 Trade Hard Materials turbo diamond blades are designed for fast precise cutting of a wide range of materials. The unique turbo rim allied with a technologically advanced bonding matrix ensures the product is designed to outperform similar priced products. Fast precise cuts & good life. Dry or wet cut. Life & performance will increase with wet cutting. Equally spaced cooling holes around the periphery of the segments keep the blade cool during cutting & dissipates the heat from the diamond matrix. The perfect choice for the enthusiast / occasional user who wants good life & speed of cut.

### **ATTRIBUTES**

- 1.5X LIFE 1.5X SPEED
- HIGH QUALITY DIAMOND GRIT
- LATEST BOND TECHNOLOGY
- ENHANCED PERFORMANCE & LIFE
- FULLY HARDENED & HEAT TREATED STEEL CORE
- GOOD SPAN OF APPLICATION & CUT
- FAST & PRECISE CUT
- TURBO SEGMENT
- VENTED COOLING HOLES FOR RAPID HEAT DISPERSION.

#### **APPLICATION**



HARD FACING BRICK, CLAY PAVERS, VITRIFIED CLAY PIPES, CLAY ROOF TILES, QUARRY TILES, TERRACOTTA, INDIAN STONE (KOTA), TRAVERTINE, PORPHYRY, CLASS B ENGINEERING BRICK 75N/MM², HARD SLATE, RIVER GRAVEL CONCRETE, LIGHT REINFORCED CONCRETE, BASALT, CONCRETE CURBS, CONCRETE SLABS, LIGHT REINFORCED CONCRETE LINTELS, HARD LIMESTONE, LIMESTONE AGGREGATE CONCRETE, CONCRETE PAVERS, CONCRETE PIPE, CONCRETE ROOF TILE.



DENSE CLAY PIPE, CLASS A ENGINEERING BRICK 125 N/MM², MEDIUM FACING BRICK, SOFT FACING BRICKS, REFRACTORY BRICK, CONCRETE BLOCKS OVER 15N/MM², HARD SANDSTONE (FINE GRIT), SOFT SLATE, MARBLE, MEDIUM SANDSTONE (MEDIUM GRIT).



GRANITE, HEAVILY STEEL REINFORCED CONCRETE, CRITICALLY HARD AGGREGATE CONCRETE (FLINT, CHERT), HARD TO MEDIUM AGGREGATE CONCRETE (CHERT - TRAP ROCK - RIVER GRAVEL), MEDIUM AGGREGATE CONCRETE (TRAPROCK - QUARTZ), MEDIUM SOFT AGGREGATE CONCRETE (GRANITE - LIMESTONE), CONCRETE WITH MEDIUM SHARP SAND, PLASTER - GROUT.

\*

SOFT SANDSTONE (COARSE GRIT), CONCRETE SCREED, CONCRETE BLOCK UNDER

PRODUCT		DIAMETER		SEGMENT HEIGHT		SEGMENT WIDTH		MAIN ARBOR - Bore		REDUCING RINGS INCLUDED		MACHINES USED
PART NO	CODE NO	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	ММ	INCH	
DA30300	MXT30105	105	4	10	0.394	2	0.079	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20, 20 - 5/8	
DA30301	MXT30110	110	4 1/3	10	0.394	2	0.079	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20, 20 - 5/8	
DA30302	MXT30115	115	4 1/2	10	0.394	2.2	0.087	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20mm, 7/8 - 5/8	
DA30303	MXT30125	125	5	10	0.394	2.4	0.094	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20mm, 7/8 - 5/8	
DA30304	MXT30150	150	6	10	0.394	2.4	0.094	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20mm, 7/8 - 5/8	
DA30305	MXT30180	180	7	10	0.394	2.5	0.098	22.23	7/8	DM - 15.88, 22.23 - 20	DM - 5/8, 7/8 - 20mm	
DA30306	MXT30230	230	9	10	0.394	2.6	0.102	22.23	7/8	22.23 - 20, 22.23 - 15.88	7/8 - 20mm, 7/8 - 5/8	
DA30307	MXT30250	250	10	10	0.394	2.8	0.110	25.4	1+P	N/A	N/A	
DA30308	MXT30300	300	12	10	0.394	3	0.118	20	20mm	N/A	N/A	
DA30309	MXT30350	350	14	10	0.394	3.2	0.126	25.4+P	1+P	25.4 - 20	1 - 20mm	<b>MA</b>




























©2023 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" & Cat "Modern Hex" trade dress as well as corporate & product identity used herein, are trademarks of Caterpillar & may not be used without permission. C6 DIAMOND LLC, a licensee of Caterpillar Inc.

SILICA DUST: Workers who are exposed to respirable crystalline silica dust are at increased risk of developing serious silica-related diseases. It is necessary to use saws & other machinery that is equipped with an integrated water delivery system that continuously feeds water to the blade. Operate & maintain all tools in accordance with manufacturer's instructions to minimize dust emissions & always wear the correct ventilator. For more info visit:

www.osha.gov/sites/default/files/publications/0SHA3681.pdf

